

Interbuild Hardwax Oil is a premium quality Wax oil specially formulated to use on wooden butcher blocks, chopping/cutting boards, soup and salad bowls and other wood applications which require a food-contact safe finish, yet easy to apply and maintain. After fully dry, it meets Non-Toxic European Standard EN71 P3, Tested and approved for contact with food stuff as per US FDA 21 CFR 175.300. All colorants used in our ZERO % VOC Hardwax oils are certified non-toxic by EN71-P3 and REACH. See www.interbuild.eu/hardwaxoil for more info and Certificates.

Interbuild Hardwax Oil provides an aesthetic and protective finish while enhancing the woody structure's consumer appeal.

PREPARATION: Prepare the wood for finishing by sanding with #180 and then #240 grit sand paper in the direction of the grain. Before applying oil, remove all sanding dust, dirt, grease or glue with a vacuum and rag.

DIRECTIONS:

1. Stir the can well.
2. Apply evenly and thoroughly with a roller/brush.
3. Wipe off lightly and excess with a soft and clean cloth.

Note: As routine oil maintenance, apply one coat of oil is sufficient.

4. Prior to re-coating lightly sand with #400 grit sand paper.
5. Repeat steps 1-4, allow 72 hours drying prior to use.
6. Color appearance varies according to number of coats applied, variation in timber color & absorption.
7. Always use a soft sponge with light detergent to clean the surface.

NOTE: WIPE OFF THE EXCESS OIL HARD WITH A COTTON CLOTH WITHIN 3-5 MINUTES FROM APPLICATION, IN ORDER TO GET A SMOOTH WAXED SURFACE!

DO NOT USE SCOTCH BRITE, DO NOT IMMERSE IN WATER / WASH IN DISHWASHER.

APPLICATION TIPS: Apply at room temperature (10-35°C). Interbuild Hardwax Oil is a ready to use product. Do not thin. if desired, use additional coats to build a finish. When used on objects with small openings, such as canisters, proper drying may be inhibited when applied on internal surface or allow longer dry time.

WARNING: Used rag/fabric/sponge must be soaked thoroughly in water and dispose off immediately in a fire safe place after use. If left unattended, they could burn spontaneously and could result in fire hazard.

COVERAGE: 1 Ltr (33.8 fl oz US) covers 20-40 m² (215.3-430.5 ft²).

CLEAN UP of tools: USE mineral turpentine.

PRECAUTION: Do not swallow and get in eyes. Wear safety glasses and use only on a well-

ventilated area. Keep out off reach of children.

FIRST AID TREATMENT: Please refer to the Material Safety Data Sheet can be obtained at our website www.interbuild.eu/hardwaxoil

CARE: All wood oils will dry with time and depending on the frequency for use of the product.

For countertops, re-oiling once or twice per year should be sufficient. For chopping boards more often.

TIPS: The finished product needs re-oiling when a water droplet smudges on the surface rather than stays as a drop.

Use a damp cloth for cleaning of ready surfaces.

WHEN USED OUTDOOR

1. Keep furniture indoor over winter or cover with a plastic cover.
2. For Algae and Fungus removal, use a hard brush and water! When dry, apply another coat of Hardwax Oil.
3. Maintain with a new coat once or twice per season.
4. For Decking, and Deck Tiles staying outside over winter, cleaning and re-oiling should be done both at start and end of season.